

## T/RH SENSOR





- measures temperature and relative humidity
- 2 up to 3km / 1.9mi range
- 3 IP42 class
- 4 up to 10 years of battery life
- flexibility of installation

business critical information for food manufacturing, warehouses / storage facilities, horticulture, building management and others.

Aranet T/RH sensor Datas	heet	
Measurements	Temperature Relative Humidity	
Line of Sight Range	3km / 1.9mi	
Operating environment	Indoor and Outdoor use	
Transmitter power	14 dBm	
Frequency	Depends on base station instructions	
Measurement Range	Temperature (-40°C to 60°C / -40°F to 140 °F) Relative humidity (0% to 100%)	
Temperature measurement accuracy	-10°C to 60°C / 14°F to 140°F	
Response time	T63% - 10 minutes at 1 m/s airflow	
Relative Humidity measurement accuracy	0 to 80% @ 30°C / 86°F 4%RH 80% to 95% @ 30°C / 86°F 6%RH	
Data Transmission	1, 2, 5, 10 minutes*	
Data Protection	Data encryption	
Power options	2 AAA Alkaline batteries (Zn/Mn0 <sub>2</sub> ) 2 AAA Lithium batteries (Li/FeS <sub>2</sub> )	
Battery life @20°C / 68°F	Up to 7 years with Alkaline batteries Up to 10 years with Lithium batteries	
Operating temperature	-20°C to 55°C / -4°F to 131°F with Alkaline batteries -40°C to 60°C / -40°F to 140°F with Lithium batteries	
Operating humidity	0% to 100% non-condensing**	
Dimensions	115x44x25mm / 4.5"×1.7"×1"	
Weight	65g / 2.3oz with Alkaline batteries 57g / 2oz with Lithium batteries	
Construction	ASA Plastic	
Protection class	IP42	
Marking	CE, FCC, IC	
Compatible base stations	Aranet PRO and Aranet MINI	
Included	2 AAA Alkaline batteries, string	
Part number	TDSPT001 (EU), TDSPT0U1 (NA), TDSPT0R1 (RU)	

 $<sup>\</sup>star$  1, 2, 5, 10 min interval supported from Aranet PRO v1.3.2 and Aranet MINI v3.20.

For more detailed information about Aranet products visit <a href="www.aranet.com">www.aranet.com</a>, contact your Aranet representative or write to info@aranet.com. Product specifications are subject to change without prior notice. Copyright © 2019 SAF Tehnika, JSC. All rights reserved.



<sup>\*\*</sup> For best accuracy, recommended operating range is 20% to 80% RH (non-condensing) and 5°C to 60°C (41°F to 140°F). Prolonged operation beyond these ranges may result in a shift of sensor reading, with slow recovery time.